

# Pur Stick

Pur Stick is the professional foaming adhesive system that adheres and bonds materials into place, sealing and stopping the passage of air, gases, water, dust, fibers and sound.

- **BONDS MOST MATERIALS**
- **PROFESSIONAL CONTROL**
- **SUBFLOOR ADHESIVE**
- **DRYWALL ADHESIVE**



Gun accessories available:



Pageris Gun

Pur Pistol

Pur Shooter

Shown with optional Pageris gun

## BENEFITS

- Labor Savings
- Low Cost
- Complete Control
- Unlimited Start-ups and Closures

## FEATURES

- Eliminates Squeaks
- Professional Pageris Foam Gun
- High Volume
- Sound Deadening

## HIGHLIGHTS

- Equivalent to 10-20 quart tubes of standard construction adhesive
- Tested and Approved  
ASTM: C-557  
APA: AFG-01

**Todol Products, Inc.**

<http://www.todol.com>

email: [info@todol.com](mailto:info@todol.com)

## Description:

PUR STICK is an aerosol, moisture curing urethane adhesive. Pur Stick is an easier and more professional way of solving your adhesive needs. Pur Stick can be used on plywood, lumber, OSB, fiberglass, foam-board, tile, particle board and most other construction materials. Pur Stick has been tested extensively by PFS/TECO, a leading testing facility. Pur Stick has passed the ASTM C-557 and the American Plywood Association's AFG-01. This can is equivalent to 10-20 quart tubes of caulking construction adhesive. Pur Stick also eliminates squeaks on subfloor gluing applications. Pur Stick is a real tool that reduces labor time.

## Benefits:

Pur Stick bonds to most construction materials, like:

### Subfloor

### Lumber

### OSB

### Fiberglass

### Foamboard

### Tile

### Particle Board

### Metals

## How to Use:

1. Shake the can well.
2. Thread the can into the adapter on the top of the gun—DO NOT OVERTIGHTEN.
3. Pull the trigger for about 5 seconds to purge all air and moisture out of the gun.
4. Clean the area thoroughly. Pur Stick bonds better to clean, dry surfaces.
5. Select the bead size by interacting between the trigger and the flow adjustment screw.
6. The can should be in a vertical position over the gun when foaming.
7. Tighten the flow adjustment screw for storage.
8. To replace an empty can, unscrew the empty can and promptly screw a replacement can into the adapter. If no replacement is available, leave the empty can in place until a replacement is at hand. ALWAYS KEEP A CAN OF FOAM ADHESIVE ON THE GUN. FAILURE TO DO THIS WILL ALLOW FOAM TO CURE AND RESULT IN PERMA-

### Visit our web site:

<http://www.todol.com>

### Contact us via email:

email: [info@todol.com](mailto:info@todol.com)

## NENT DAMAGE TO THE GUN.

9. Periodically flush our Gun Cleaner through the gun for good maintenance.
10. Best performance is obtained when the can temperature is 60° – 80° F

### Use in Hot Weather

1. Shake the can for 30 seconds.
2. Lay out practice beads.
3. Mist the area with water.

### Use in Cold Weather

1. Warm the can to room temperature—60°F to 80°F.
2. Shake the can for 30 seconds.
3. Mist the area with water.

## Subfloor Application Suggestions

1. Shake can well
2. Can temp 60 - 80° F.
3. Mist stud with water
4. Lay down a one inch bead
5. Expose bead to the moisture in the air for 5-7 minutes
6. Carefully place the flooring down on the stud without the need of kicking in place
7. Do not pick up the flooring from the stud once the flooring has been put down

## Stopping Squeaks in Existing Floors

1. Shake can well
2. Can temp 66 - 80° F
3. Place green plastic needles on the tip of the Pageris foam gun
4. Foam a small bead between the stud and flooring to fill the void
5. Keep the can as vertical as possible in the tight area from under the flooring
6. Call for details-

## Safety Recommendations:

Due to possible production of highly flammable vapor/air mixtures, provide sufficient ventilation. Do not smoke. Keep out of reach of children. In case of eye contact, rinse with plenty of water and seek medical advice. In case of skin contact, wash off with plenty of water and soap.

## Helpful Hints

1. Always keep a can on the gun. Never leave the gun without a can on it, this will clog the gun.
2. Mist the area with water before foaming.
3. Can temperature must be 60° – 80°F
4. Shake can well.
5. Periodically flush gun with Todol Gun Cleaner. **Warning:** Overuse of cleaner will permanently damage gun.
6. For large cross action, layer then mist with water, another foam layer then mist, etc.
7. Always foam with can vertical.
8. Tighten set screw when finished foaming.

Wear suitable protective gloves and goggles during work. In case of accident or if you feel unwell, seek immediate medical advice (if possible, show this label.)

Container is pressurized. Protect from sunlight and temperatures above 50° C. Do not pierce or burn even after use. Do not spray against flames or incandescent objects.

Harmful when inhaled. Irritates eyes, respiratory organs and skin. Can result in sensitization when inhaled. Can produce highly flammable vapor/air mixture during use.

## Limited Warranty:

The manufacturer will replace at no charge to purchaser any product proven to be defective. The warranty is limited to replacement of material only, and no liability is assumed for use of this product by the purchaser, or for any consequential damages arising from its use in any form whatsoever.

## Contains:

Polyol prepolymer CAS 59675-67-14  
Monomeric diphenylmethane diisocyanate (MDI) CAS 1010-68-8,  
Tetrafluoroethane, Dimethyl ether, butane/propane. MDI can irritate eyes, respiratory organs and skin. Some after exposure may be sensitized to MDI.

## Todol Products, Inc.

20 Charles Street

P.O. Box 398

Natick, MA 01760

Phone: 508-651-3818

Fax: 508-651-0729

Manufactured in Germany

Consumer Commodity ORM-D